

# NanoBracket® for NBE-M5-19

BRACKET FOR NANOBEAM® M5-19 AND 5AC-19

NanoBracket for NBE-M5-19 is our 2nd Generation mounting system for 5GHz/19dBi NanoBeam CPE from UBNT. This NanoBracket has a solid base made of die cast aluminum and allows for 140° of smooth and precise adjustment in azimuth, elevation and rotation using our original ball hinge.

Large mounting surface and all stainless steel hardware make the overall robustness of the bracket SOLID.



## TECHNICAL DATA

|                        |  |
|------------------------|--|
| Materials              | Bracket - UV stabilized and weather resistant ABS plastic<br>Holder - ADC 12<br>Hardware - Stainless Steel |
| Flame Rating           | UL 94 HB   |
| Pole Mounting Diameter | 50-70 mm   |
| Wall Mounting          | Yes  |
| Operating Temp.        | -30 to + 60 °C   |
| Wind Survival          | 120 Km/h   |
| Weight                 | 0.3 Kg / 0.68 lbs – single unit incl. package<br>16.4 Kg / 36.16 lbs – carton (50 units)                   |
| Single Unit            | Retail Box: 9 × 9 × 15 cm  |
| 50 units               | Carton Box: 48 × 34 × 47 cm  |

## COMPATIBLE WIRELESS PLATFORMS

|                    |                                     |
|--------------------|-------------------------------------|
| Ubiquiti Networks™ | NanoBeam® 5AC-19<br>NanoBeam® M5-19 |
|--------------------|-------------------------------------|

## PACKAGE CONTENTS

- Bracket Body
- Holder
- Screw 3,5 x 45 mm (4 pcs)
- Wall Plug (4 pcs)
- Hose Clamp (1pc)

## PRODUCT DIMENSIONS

